

**- WR BOTTOM METAL (DBM), TRIGGER GUARD FLOORPLATE.  
- STEYR SSG 69 CONVERSION TO AICS SHORT ACTION PATTERN MAGAZINE**



- DESCRIPTION:**
- This item is the bottom metal, trigger guard and floorplate in one piece that screws into the bottom of the stock of a factory SSG 69.
  - Drop in fit - NO modifications to the stock or rifle are required.
  - Note, this is made standard for a single trigger rifle. Double trigger rifle simply has the trigger lever thru hole extended (simple mill or file should get the job done).
- SPECIAL FEATURES:**
- Made to fit the standard off shelf stock configuration without modification (drop in fit).
  - Extended mag release. - All Metal construction. - Oversize trigger guard (shoot with glove).
- SUITABLE FOR USE:**
- This unit requires MDT metal magazines with front binder plate. The binder plate spaces the front of the bullet tip back enough to pass the front floorplate feed ramp and mag stop. No other magazine should be used, unless it directly copies the above MDT mag.
- EQUIPMENT NEEDED:**
- Driver bits to remove the factory DBM, and drop-in install the WR unit.
  - If the trigger slot needs to be increased for a 2<sup>nd</sup> trigger, a file or similar...
- ITEM INCLUSIONS:**
- No inclusions. This DBM is a straight swap.
- POSITIONING:**
- Replaces the factory DBM in the same position and orientation.
- FITTING:**
- Remove factory DBM assembly.
  - Insert the WR DBM in the stock inlet. This unit only goes one way.
  - Use of the factory screws and screw up to pinch tight.
  - Torque up to approximately 6Nm (4.5 ft-lbs or 54 in-lbs), then adjust accordingly.
- ADJUSTMENTS:**
- There should be no adjustments required, however some stocks may shrink or swell. Changing the height of the DBM in the stock may be required in relation to the required presentation height of the magazine to the receiver for a positive click into position. The magazine presentation height (top of mag retainer lips should be 1mm below bolt body. If the mag lips touches the bolt on operation, investigate of corrective action – possible to pack between stock and DBM with a (or multiple) slice of paper or remove material from the DBM footprint or stock as required.
- TESTING:**
- A simple dry bench test with dummy rounds should suffice.  
Dry fire activities in different simulated field shooting positions to ensure correct function.
- SERVICING & MAINT**
- Keep clean and lightly lubricate the release lever.
  - Ensure reasonable release lever spring tension.
- SPARE PARTS:**
- [www.watersrifleman.com](http://www.watersrifleman.com) with any enquiries.
- RELATED ITEMS:**
- Factory T3 and T3x factory pattern magazines, including WR mags.  
Mags by other companies/brands should be tested or investigation done before buying.  
Note, the WR expandable bolt on bottom pic rail fits simply with the single front screw.  
This WR bottom pic rail can be used to fit all underneath furniture (flashlight, carry grips, etc).